

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)*(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.
FQ5-488

Total Pages in this Submission

TO THE ASSISTANT COMMISSIONER FOR PATENTSBox Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

TELEPHONE APPARATUS AND ALERT CONTROL METHOD

and invented by:

Yoichi OkanoIf a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements☒ Filing fee as calculated and transmitted as described below2. ☒ Specification having 35 pages and including the following:

- a. ☒ Descriptive Title of the Invention
- b. ☐ Cross References to Related Applications *(if applicable)*
- c. ☐ Statement Regarding Federally-sponsored Research/Development *(if applicable)*
- d. ☐ Reference to Microfiche Appendix *(if applicable)*
- e. ☒ Background of the Invention
- f. ☒ Brief Summary of the Invention
- g. ☒ Brief Description of the Drawings *(if drawings filed)*
- h. ☒ Detailed Description
- i. ☒ Claim(s) as Classified Below
- j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.

FQ5-488

Total Pages in this Submission

Application Elements (Continued)

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*

- a. ☐ Formal Number of Sheets _____
- b. ☒ Informal Number of Sheets 14 (Fig. 1-17)

4. ☒ Oath or Declaration

- a. ☒ Newly executed *(original or copy)* ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).

- ☐ Incorporation By Reference *(usable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.

- ☐ Computer Program in Microfiche *(Appendix)*

- ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*

- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☐ Certificate of Mailing
- ☐ First Class ☐ Express Mail *(Specify Label No.):* _____

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
FQ5-488

Total Pages in this Submission

Accompanying Application Parts (Continued)

15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*


16. ☐ Additional Enclosures *(please identify below):*

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra		Rate	Fee
Total Claims	20	- 20 =	0	x	\$18.00	\$0.00
Indep. Claims	6	- 3 =	3	x	\$78.00	\$234.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>						\$0.00
BASIC FEE						\$690.00
OTHER FEE (specify purpose)						\$0.00
TOTAL FILING FEE						\$924.00

- ☒ A check in the amount of \$924.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 50-0481 as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of _____ as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature

Sean M. McGinn
Registration No. 34,386
Customer No. 21254

Dated: September 27, 2000

CC:

TELEPHONE APPARATUS AND ALERT CONTROL METHOD

BACKGROUND OF THE INVENTION

1. Field of the invention

The present invention generally relates to a telephone apparatus such as a portable or mobile telephone, and in particular to a telephone apparatus having a communication history memory and an alert control method thereof.

2. Description of the Related Art

There has been proposed a telephone set having a communication history memory which is used to allow a user to check the communication history that is a sequential list of the calling and called times of day and the phone numbers of the other parties thereof. Accordingly, by requesting the communication history through an input device such as a keypad, the user is notified when communication was made with a certain person.

15 However, when the user forgets to check the communication history, a certain person who called to the user would be left in a state that no word has been heard in reply.

In Japanese Patent Application Unexamined Publication No. 8-181781, a voice mail system using a PHS (personal-handly phone
20 system) terminal has been disclosed, which allows the user to

FQ5-488

2

check the status of its mailbox without telephoning the voice mail system. More specifically, when receiving a voice mail addressed to a subscriber, a service management office transmits an incoming-call occurrence notification, the incoming-call occurrence time of day, and the caller phone number of the incoming call to the PHS terminal of the subscriber. Based on the incoming-call occurrence time of day received from the service management office, the PHS terminal determines whether a voice mail that its predetermined hold time has elapsed exists in the mailbox. If such a voice mail exists, then the PHS terminal alerts the user by audible or silent alert to the presence of such a voice mail that its predetermined hold time has elapsed.

According to this conventional voice mail system, the user can be alerted about an incoming call only. Therefore, communication with a certain person cannot be ensured sufficiently.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a telephone apparatus and an alert control method allowing communication with a certain person to be ensured.

According to the present invention, when an elapsed time after the last-communication time of day with a certain person

FQ5-488

3

exceeds a predetermined time interval, the telephone apparatus alerts the user.

According to an aspect of the present invention, an alert control method in telephone equipment having an alert function, includes the steps of: a) storing time data related to a name of a person to communicate with in a phonebook database; b) determining based on the time data whether a predetermined time interval has elapsed without communicating with the person; and c) alerting when it is determined that the predetermined time interval has elapsed without communicating with the person. The time data may be a last-communication time of day at which communication with the person was made last.

The step (b) may include the steps of: b.1) reading a current time of day from a timer; b.2) calculating an elapsed time from the last-communication time of day to the current time of day; and .3) determining whether the elapsed time exceeds the predetermined time interval.

The last-communication time of day may be initially set to a time of day when data related to the person is registered into the phonebook database. The last-communication time of day may be updated each time communication with the person is terminated. The predetermined time interval may be arbitrarily determined depending on a user's instruction.

The alerting of the step (c) may be performed by driving at least one of a speaker, a vibrator, and a display.

FQ5-488

4

According to another aspect of the present invention, an alert control method includes the steps of: a) storing a last-communication time of day related to a name of each of a plurality of persons to communicate with in a phonebook database; b) dividing the plurality of persons into a plurality of groups; c) determining a before-alert time interval for each of the groups, wherein the before-alert time interval is a time interval during which communication with the person is not made before alerting; d) determining whether the before-alert time interval has elapsed after the last-communication time of day; and e) alerting when it is determined that the before-alert time interval has elapsed after the last-communication time of day.

According to further another aspect of the present invention, an alert control method includes the steps of: a) storing time data related to a name of a person to communicate with in a phonebook database; b) storing an alert-inhibition time period during which alert is inhibited; c) determining based on the time data whether a predetermined time interval has elapsed without communicating with the person; d) alerting when a current time of day falls out of the alert-inhibition time period and it is determined that the predetermined time interval has elapsed without communicating with the person; and e) inhibiting alert when the current time of day falls into the alert-inhibition time period even if it is determined that the predetermined time interval has elapsed without communicating with the person.

FQ5-488

5

In the step (e), an audible alert by the speaker and/or the vibrator may be inhibited and a silent alert on the display may be permitted.

According to still another aspect of the present invention,
5 the alert control method further includes the steps of: storing an alert list containing persons targeted for alert; and displaying the alert list in form of a menu on a display so that a desired one is selected from the alert list to make a call to the desired one.

10 A telephone apparatus according to the present includes: a phonebook database for storing time data related to a name of a person to communicate with; and a controller for determining based on the time data whether a predetermined time interval has elapsed without communicating with the person and starting the
15 alert function when it is determined that the predetermined time interval has elapsed without communicating with the person.

A telephone apparatus according to the present includes: a phonebook database for storing a last-communication time of day related to a name of each of a plurality of persons to
20 communicate with, wherein the plurality of persons is divided into a plurality of groups; and a controller for determining a before-alert time interval for each of the groups, wherein the before-alert time interval is a time interval during which communication with the person is not made before alerting.
25 determining whether the before-alert time interval has elapsed

F05-488

6

after the last-communication time of day, and starting the alert function when it is determined that the before-alert time interval has elapsed after the last-communication time of day.

A telephone apparatus according to the present includes:

- 5 a phonebook database for storing time data related to a name of a person to communicate with; an alert-inhibition timetable storing an alert-inhibition time period during which alert is inhibited; and a controller for determining based on the time data whether a predetermined time interval has elapsed without
10 communicating with the person, starting the alert function when a current time of day falls out of the alert-inhibition time period and it is determined that the predetermined time interval has elapsed without communicating with the person, and inhibiting alert when the current time of day falls into the alert-inhibition
15 time period even if it is determined that the predetermined time interval has elapsed without communicating with the person.

As described above, according to the present invention, when an elapsed time after the last-communication time of day with a certain person exceeds a predetermined time interval, the
20 telephone alerts the user. Therefore, in the case where the phone number of a registered person has not been used for a long time or the registered before-alert time interval, the user is alerted and thereby the communication with that person is promoted.

Further, a plurality of registered names are divided into
25 a plurality of groups and a before-alert time interval can be

7

set for each registration group, resulting in improved operability and enhanced convenience.

Furthermore, an alert-inhibition time period can be set to a desired time period. Therefore, beeper sound or vibration is prevented from annoying the people around the telephone in conference or in sleep.

Finally, the user is alerted and thereafter the alerting image is changed to an easy-to-call alerting image including a list of persons so as to easy make a call to a desired one of the listed persons.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a radio mobile telephone that is an embodiment of a telephone apparatus according to the present invention;

15 Fig. 2 is a flowchart showing an alert registration
operation according to a first embodiment of the present
invention;

Fig. 3 is a flowchart showing an alert control operation according to the first embodiment of the present invention;

Fig. 5 is a flowchart showing an operation of updating the last-access time of day to the other party when the telephone originates a call in the first embodiment of the present invention:

Fig. 7 is a diagram showing an example of contents of the phonebook database in the first embodiment of the present invention;

Fig. 9 is a flowchart showing an alert registration operation according to the second embodiment of the present invention;

FQ5-488

9

Fig. 10 is a diagram showing an example of contents of the phonebook database in the second embodiment of the present invention;

Fig. 11 is a diagram showing an example of an alert-inhibition timetable according to a third embodiment of the present invention;

Fig. 12 is a flowchart showing an alert control operation according to the third embodiment of the present invention;

Fig. 13 is a diagram showing an operation of setting alert-inhibition time periods according to the third embodiment of the present invention;

Fig. 14 is a diagram showing an example of a displayed alert image according to the first to third embodiments of the present invention;

Fig. 15 is a diagram showing an example of a displayed menu of registered persons to communicate with according to the first to third embodiments of the present invention;

Fig. 16 is a diagram showing an example of an alert list

004260 2426960

FQ5-488

10

according to a fourth embodiment of the present invention; and

Fig. 17 is a flowchart showing a calling operation using the alert list according to the fourth embodiment of the present invention.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Fig. 1, there is shown a mobile telephone in accordance with the present invention. The mobile telephone is provided with a radio system 20, which transmits and receives a radio signal to and from a radio base station (not shown) under control of a control section 10. The control section 10 includes a program-controlled processor such as a central processing unit (CPU). A control program for the mobile telephone is stored in a read-only memory (not shown) and runs on the program-controlled processor of the control section 10 to control all operations of the mobile telephone including an alert control operation as described later.

The mobile telephone is further provided with a memory 30 including a phonebook (phone directory) database 110 and other timetables, which can be accessed by the control section 10. As described later, the phonebook database 110 retrievably stores a plurality of telephone numbers and related data as shown in

PQ5-488

11

Fig. 7.

An input device 40 such as a keypad including a ten-key is provided on the main surface of a housing of the mobile telephone. The input device 40 is used by the user to enter various instructions such as registering of a new telephone number, retrieval of a telephone number, dialing of a selected telephone number and other necessary operations.

A speaker 50 is used to generate reception voice and an audible alert for notifying the user of incoming call or for alerting the user that communication with a certain person has not been made during a preset time interval. It is the same with a vibrator 90. A microphone 60 is used to input transmission voice.

Necessary information is displayed on a display 70 under control of the control section 10. The display 70 may employ a liquid-crystal display (LCD) or light-emitting diodes (LEDs).

A timer 80 outputs a current time of day or other time data to the control section 10. The control section 10 uses time data from the timer 80 to determine the incoming-call occurrence time of day, the originating-call occurrence time of day, the communication termination time of day, a communication time, and to calculate an elapsed time after the last-communication time of day for each entry in the phonebook database 110. As described later, when an elapsed time after the last-communication time of day for a registered person exceeds a preset time interval,

FQ5-488

12

the control section 10 drives the speaker 50, the vibrator, or the display 70 or a combination thereof to notify the user that communication with that person has not been made during the preset time interval. This causes the user to be prevented from forgetting to get contact with that person.

FIRST EMBODIMENT

A first embodiment of the present invention will be described hereafter with reference to Figs. 1-7.

Alert registration

Referring to Fig. 2, a user of the mobile telephone as shown in Fig. 1 manually operates the input device 40 to enter an alert registration request. The control section 10 monitors the input device 40 to determine whether the alert registration is requested (step 201). If it is determined that the alert registration is requested (YES at step 201), the control section 10 prompts on the display 70 the user to select a name targeted for alert to silence and enter a time interval before alerting. When the user selects the name and enters the before-alert time interval (step 202), the control section 10 searches the phonebook database 110 for the selected name and associates the before-alert time interval with information related to the selected name to store it into the phonebook database 110 as shown in Fig. 7 (step 203).

If it is determined that the alert registration is not requested (NO at step 201), the control section 10 further

FQ5-488

13

determines whether the user requests to delete an existing alert registration (step 204). When alert registration deletion is requested (YES at step 204), the control section 10 prompts the user on the display 70 to enter a name targeted for alert registration deletion. When the user uses the input device 40 to select the name targeted for alert registration deletion (step 205), the control section 10 searches the phonebook database 110 for the selected name and resets the alert registration associated with the selected name to "no setting" to delete the alert registration (step 206). When alert registration deletion is not requested (NO at step 204), the alert registration is terminated without any change to the phonebook database 110.

Taking as an example the case where "Yamada Taro" registered in the phonebook database 110 is set to alert registration such that alert is made after three days of silence (see Fig. 7). The user selects the alert registration at the step 201 and selects "Yamada Taro" as a person targeted for alert registration and enters "three days" as the before-alert time interval at step 202. The control section 10 searches the phonebook database 110 for the selected name "Yamada Taro" and associates the before-alert time interval "three days" with information related to the selected name "Yamada Taro" to store it into the phonebook database 110 as shown in Fig. 7.

Taking as an example the case where "Sato Eisaku" registered in the phonebook database 110 is set to alert

F05-488

14

registration deletion. The user uses the input device 40 to select the name "Sato Eisaku" targeted for alert registration deletion at step 205. The control section 10 searches the phonebook database 110 for the selected name "Sato Eisaku" and
5 resets the alert registration associated with the selected name "Sato Eisaku" to "no setting" to delete the alert registration at step 206.

Alert control

Referring to Fig. 3, the control section 10 determines
10 whether alert to silence has been already registered (step 301). If no alert to silence is registered (NO at step 301), the alert control is completed.

When the alert to silence has been already registered (YES at step 301), the control section 10 sequentially checks entries
15 in the phonebook database 110 to determine whether the before-alert time interval has been set (step 302). If the before-alert time interval of an entry has been reset to "No setting" (NO at step 302), the control section 10 shifts the alert control to the next entry (step 308).

20 If the before-alert time interval of an entry has been set (YES at step 302), then the control section 10 reads the current time of day from the timer 80 (step 303). Thereafter, the control section 10 reads the last-access time of day when last
25 communicated with the person of a selected entry from the phonebook database 110 (step 304). Then, the control section

002260 24859560

FQ5-488

15

10 calculates the time period of silence elapsed after the last-access time of day (step 305) and determines whether the elapsed time exceeds the before-alert time interval that has been set (step 306).

- 5 If the elapsed time exceeds the before-alert time interval (YES at step 306), the control section 10 alerts the user that the before-alert time interval of silence has elapsed by displaying alert information on the display 70 and driving the speaker or the vibrator (step 307). Thereafter, the control
- 10 section 10 shifts the alert control to the next entry (step 308) and repeatedly performs the steps 301-308 until all entries have been checked.

- Taking as an example the case where the before-alert time interval of "Suzuki Ichiro" has been set to 15 hours (see Fig.
- 15 7). When having selected the entry of "Suzuki Ichiro", the control section 10 reads the current time of day from the timer 80 at step 303. Here, it is assumed that the current time of day is 1999/06/01/10:06, that is, 10:06, June 1st, 1999.
- Thereafter, the control section 10 reads the last-access time
- 20 of day with "Suzuki Ichiro" from the phonebook database 110 at step 304. Here, the last-access time of day with "Suzuki Ichiro" is 1999/05/31/19:05. Therefore, the time period of silence elapsed after the last-access time of day is 15 hours and 1 minute.
- The control section 10 determines that the time period of silence
- 25 exceeds the before-alert time interval of 15 hours at step 306.

PQ5-488

16

Therefore, the control section 10 alerts the user by displaying alert information on the display 70 and driving the speaker or the vibrator at step 307.

Data entry

5 Referring to Fig. 4, when registration of data of a person to communicate with is requested (YES at step 401), the control section 10 prompts the user to enter necessary data of the person to communicate with. When the necessary data including at least the name and phone number of the person has been entered by the
10 user operating the input device 40 (step 402), the control section 10 reads the current time of day from the timer 80 (step 403). Then, the control section 10 associates the entered data of the person with the time of day read from the timer 80 when the necessary data has been entered by the user and stores these data
15 into the phonebook database 110 (step 404).

When the before-alert time interval has not been entered at the step 402, the before-alert time interval of the person in the phonebook database 110 is set to "No setting".

For example, in the case where phone number "070-4416-
20 5525", the name "Nishida Hikari" and the before-alert time interval "1 month (30 days)" are entered into the phonebook database 110 at 15:22, May 25, 1999, the data of "Nishida Hikari" is stored in the phonebook database 110 as shown by the third entry (No. 3) of Fig. 7.

FQ5-488

17

Update of last-access time of day

The update operation of the last-access time interval in the case where the user originates a call to the other party will be described hereafter. It should be noted that the update
5 operation is not performed when the before-alert time interval is set to "No setting".

Referring to Fig. 5, the control section 10 determines whether the phonebook database 110 is used to make a call (step 501). In the case where the user selects the phonebook database
10 110 to make a call (YES at step 501), the control section 10 prompts the user to search the phonebook database 110 for a person to be called. When the user selects a person to be called and enters a calling instruction (step 502), the control section 10 stores the data of the selected person to be called into the memory 30
15 so as to perform a redial function or the like (step 503). Thereafter, the control section 10 performs calling control (step 504) and communication control (step 505). The communication operation is kept (NO at step 506) until the communication is terminated.

20 When the communication is terminated by one of the calling party and the other party (YES at step 506), the control section 10 performs a termination operation (step 507). Then, the control section 10 determines whether the before-alert time interval of the other party is set to "No setting" (step 508).
25 When the before-alert time interval of the other party is not

FQ5-488

18

set to "No setting" (NO at step 508), the control section 10 reads the time of day at which the communication is terminated from the timer 80 (step 509). Thereafter, the control section 10 associates the data of the other party with the termination time of day read from the timer 80 and stores these data into the entry of the other party of the phonebook database 110 (step 510). In other words, the old access time of day is replaced with the new access time of day that has been just read from the timer 80. In this way, the last-access time of day for the other party is updated.

In the case where the user does not use the phonebook database 110 (NO at step 501), the control section 10 prompts the user to enter the phone number of a person to be called. When the user enters the phone number through the input device 40 (step 511), the control section 10 searches the phonebook database 110 to determine whether the entered phone number has been already registered in the phonebook database 110 (step 512). If already registered (YES at step 512), the control goes to the step 503 to store the data of the person into the memory 30. Thereafter, the steps 504-510 are performed as described above.

When the entered phone number is not registered in the phonebook database 110 (NO at step 512), the control section 10 performs the calling control (step 513) and the communication control (step 514). The communication operation is kept (NO at step 515) until the communication is terminated. When the

FQ5-488

19

communication is terminated by one of the calling party and the other party (YES at step 515), the control section 10 performs a termination operation (step 516) without updating the last-access time of day. As described before, when the

5 before-alert time interval of the other party is set to "No setting" (YES at step 508), the control section 10 terminates the process without updating the last-access time of day.

Next, the update operation of the last-access time interval in the case where the user takes the call from the other party
10 will be described hereafter. It should be noted that the update operation is not performed when the before-alert time interval of the other party is set to "No setting".

Referring to Fig. 6, the control section 10 determines whether CLIP (Calling Line Identification Presentation) function
15 has been set at the other party (step 601). In the case where CLIP function has been set at the other party (YES at step 601), the control section 10 detects the calling number of the other party and stores it into the memory 30 (step 602). Then, the control section 10 searches the phonebook database 110 to
20 determine whether the calling number of the other party has been already registered therein (step 603).

When the calling number of the other party has been already registered in the phonebook database 110 (YES at step 603), the control section 10 further determines whether the user takes the
25 call (off-hook) (step 604). When the user takes the call (YES

0042604709300

F05-488

20

at step 604), the control section 10 performs calling control (step 605) and communication control (step 606). The communication operation is kept (NO at step 606) until the communication is terminated.

- 5 When the communication is terminated by one of the calling party and the other party (YES at step 606), the control section 10 performs a termination operation (step 607). Then, the control section 10 determines whether the before-alert time interval of the other party is set to "No setting" (step 608).
- 10 When the before-alert time interval of the other party is not set to "No setting" (NO at step 608), the control section 10 reads the time of day at which the communication is terminated from the timer 80 (step 609). Thereafter, the control section 10 associates the data of the other party with the termination time
- 15 of day read from the timer 80 and stores these data into the entry of the other party of the phonebook database 110 (step 610). In other words, the old access time of day is replaced with the new access time of day that has been just read from the timer 80. In this way, the last-access time of day for the other party is
- 20 updated.

- When CLIP function is not set at the other party (NO at step 601) or when the calling number of the other party is not registered in the phonebook database 110 (NO at step 603), the control section 10 further determines whether the user takes the
- 25 call (off-hook) (step 611). When the user takes the call (YES

FQ5-488

21

at step 611), the control section 10 performs calling control (step 612) and communication control (step 613). The communication operation is kept (NO at step 613) until the communication is terminated. When the communication is terminated by one of the calling party and the other party (YES at step 613), the control section 10 performs a termination operation (step 614) without updating the last-access time of day. As described before, when the before-alert time interval of the other party is set to "No setting" (YES at step 608), the control section 10 terminates the process without updating the last-access time of day.

As described above, according to the first embodiment, when the phone number of a registered person has not been used for the registered before-alert time interval or more, the user is alerted and thereby the communication with that person is promoted.

SECOND EMBODIMENT

An alert control method according to a second embodiment of the present invention allows a before-alert time interval to be set for each registration group.

As shown in Fig. 8, for example, in the case of a group being "Client", the before-alert time interval is automatically set to "three days". In the case of a group being "Friend", the before-alert time interval is automatically set to "15 hours".

Referring to Fig. 9, a user of the mobile telephone as shown

FQ5-488

2 2

in Fig. 1 manually operates the input device 40 to enter an alert registration request. The control section 10 monitors the input device 40 to determine whether the alert registration is requested (step 901). If it is determined that the alert registration is requested (YES at step 901), the control section 10 prompts on the display 70 the user to select a group targeted for alert to silence and enter a time interval before alerting. When the user selects the group and enters the before-alert time interval (step 902), the control section 10 searches the phonebook database 110 for entries belonging to the selected group and replaces the before-alert time interval for each entry belonging to the selected group with the new one and store it into the phonebook database 110 as shown in Fig. 8 (step 903).

If it is determined that the alert registration is not requested (NO at step 901), the control section 10 further determines whether the user requests to delete an existing alert registration (step 904). When alert registration deletion is requested (YES at step 904), the control section 10 prompts the user on the display 70 to enter a group targeted for alert registration deletion. When the user uses the input device 40 to select the group targeted for alert registration deletion (step 905), the control section 10 searches the phonebook database 110 for the selected group and resets the alert registration associated with the selected group to "no setting" to delete the alert registration (step 906). When alert

F05-488

23

registration deletion is not requested (NO at step 904), the alert registration is terminated without any change to the phonebook database 110.

As shown in Fig. 10, for example, the user enters data such that the before-alert time interval of the group "Client" is set to "three days" and the before-alert time interval of the group "Friend" is set to "15 hours", the control section 10 automatically replaces the before-alert time interval of the entries belonging to group "Client" with "three days" and the before-alert time interval of the entries belonging to group "Friend" with "15 hours".

THIRD EMBODIMENT

An alert control method according to a third embodiment of the present invention allows an alert-inhibition time period to be set so as to prevent beeper sound or vibration from annoying the people around the telephone in conference or in sleep.

As shown in Fig. 11, an alert-inhibition time period during which alert is inhibited can be registered in an alert-inhibition timetable 120 that is provided in the memory 30. For example, as shown by the setting No. 1, the alert-inhibition time period is set to the same time period 00:00 to 08:00 every day. Further, as shown by the setting No. 2, the alert-inhibition time period may be arbitrary set to a time period from a user-designated time of day to another user-designated time of day.

Alert control

24

Referring to Fig. 12, the control section 10 determines whether alert to silence has been already registered (step 1201). If no alert to silence is registered (NO at step 1201), the alert control is completed.

5 When the alert to silence has been already registered (YES at step 1201), the control section 10 sequentially checks entries in the phonebook database 110 to determine whether the before-alert time interval has been set (step 1202). If the before-alert time interval of an entry has been reset to "No setting" (NO at step 1202), the control section 10 shifts the alert control to the next entry (step 1210).

If the before-alert time interval of an entry has been set (YES at step 1202), then the control section 10 reads the current time of day from the timer 80 (step 1203). Thereafter, the control section 10 reads the last-access time of day when last communicated with the person of a selected entry from the phonebook database 110 (step 1203). Then, the control section 10 calculates the time period of silence elapsed after the last-access time of day (step 1205) and determines whether the elapsed time exceeds the before-alert time interval that has been set (step 1206).

If the elapsed time exceeds the before-alert time interval (YES at step 1206), the control section 10 further determines from the alert-inhibition timetable 120 whether the current time of day falls into an alert permitted time period (step 1207).

FQ5-488

25

When it is permitted (YES at step 1207), the control section 10 alerts the user that the before-alert time interval of silence has elapsed by displaying alert information on the display 70 and driving the speaker or the vibrator (step 1208). When it is inhibited (NO at step 1207), the control section 10 alerts the user by only displaying alert information on the display 70 (step 1209). Thereafter, the control section 10 shifts the alert control to the next entry (step 1210) and repeatedly performs the steps 1201-1209 until all entries have been checked.

10 Assuming that the alert-inhibition time period is set to the time period from 00:00 to 08:00 every day as the setting No. 1 of Fig. 11 and the current time is "07:00", it is determined that the current time falls into the alert-inhibition time period (step 1207). Therefore, the user is alerted by only displaying
15 alert information on the display 70 (step 1209).

The alert-inhibition time period is registered into the alert-inhibition timetable 120 as described hereafter.

Referring to Fig. 13, the control section 10 determines whether the alert-inhibition time registration is requested
20 (step 1301). If it is determined that the alert-inhibition time registration is requested (YES at step 1301), the control section 10 prompts on the display 70 the user to enter the alert-inhibition time period. When the user enters the alert-inhibition time period (step 1302), the control section 10 stores it into the
25 alert-inhibition timetable 120 as shown in Fig. 11 (step 1303).

FQ5-488

26

As necessary, a plurality of alert-inhibition time periods may be registered. In this case, the user designates active one of the registered alert-inhibition time periods.

If it is determined that the alert-inhibition time registration is not requested (NO at step 1301), the control section 10 further determines whether the user requests to delete an existing alert-inhibition time registration (step 1304). When alert-inhibition registration deletion is requested (YES at step 1304), the control section 10 prompts the user on the display 70 to select an existing alert-inhibition time period to be deleted. When the user selects an alert-inhibition time period, the control section 10 deletes the selected alert-inhibition time period from the alert-inhibition timetable 120 (step 1305).

FOURTH EMBODIMENT

According to a fourth embodiment of the present invention, the user is alerted by displaying alert information on the display 70 and/or driving the speaker 50 or the vibrator 90 and thereafter the alerting image is changed to an easy-to-call alerting image.

As shown in Fig. 14, more specifically, an alerting image 160 is displayed on the display 70 provided in the housing 150 of the mobile telephone. Thereafter, as shown in Fig. 15, an easy-to-call alerting image is displayed such that the user easily makes a call to a desired one selected from a list of persons each exceeding the preset before-alert time intervals.

FQ5-488

27

Referring to Fig. 16, after alerting, the control section 10 creates an alert list 130 in the memory 30, the alert list 130 containing at least phone numbers and names of the persons each exceeding the preset before-alert time intervals. This
5 easy-to-call alerting image is maintained on screen until the user makes a call to one of the listed persons.

Referring to Fig. 17, when the easy-to-call alerting image is displayed on the display 70, the user selects a person to communicate with from the alert list displayed (step 1701). Then,
10 the control section 10 reads the phone number of the selected person from the alert list 130 and performs the calling and communication control operation (step 1702).

In this manner, the user looks at the easy-to-call alerting image on the display 70 and selects a person to communicate with
15 from the alert list displayed to make a call. Therefore, communication with a person exceeding the preset before-alert time intervals can be promoted.

It is to be understood that the present invention is not limited to the above-described embodiments and changes and
20 variations may be made without departing from the spirit of scope of the following claims.

FQ5-488

28

CLAIMS:

1. An alert control method in telephone equipment having an alert function, comprising the steps of:

a) storing time data related to a name of a person to communicate with in a phonebook database;

5 b) determining based on the time data whether a predetermined time interval has elapsed without communicating with the person; and

c) alerting when it is determined that the predetermined time interval has elapsed without communicating
10 with the person.

2. The alert control method according to claim 1, wherein the time data is a last-communication time of day at which communication with the person was made last.

3. The alert control method according to claim 2,
15 wherein the step (b) comprises the steps of:

b.1) reading a current time of day from a timer;

b.2) calculating an elapsed time from the last-communication time of day to the current time of day; and

b.3) determining whether the elapsed time exceeds
20 the predetermined time interval.

002260 2486960

FQ5-488

29

4. The alert control method according to claim 2,
wherein the last-communication time of day is initially set to
a time of day when data related to the person is registered into
the phonebook database.

5 5. The alert control method according to claim 2,
wherein the last-communication time of day is updated each time
communication with the person is terminated.

6. The alert control method according to claim 1,
wherein the predetermined time interval is arbitrarily
10 determined depending on a user's instruction.

7. The alert control method according to claim 1,
wherein the alerting of the step (c) is performed by driving at
least one of a speaker, a vibrator, and a display.

8. An alert control method in telephone equipment
15 having an alert function, comprising the steps of:

a) storing a last-communication time of day related
to a name of each of a plurality of persons to communicate with
in a phonebook database;

b) dividing the plurality of persons into a plurality
20 of groups;

002200 2489950

FQ5-488

30

c) determining a before-alert time interval for each of the groups, wherein the before-alert time interval is a time interval during which communication with the person is not made before alerting;

5 d) determining whether the before-alert time interval has elapsed after the last-communication time of day; and

e) alerting when it is determined that the before-alert time interval has elapsed after the last-
10 communication time of day.

9. The alert control method according to claim 8, wherein the last-communication time of day is initially set to a time of day when data related to the person is registered into the phonebook database.

15 10. The alert control method according to claim 8, wherein the last-communication time of day is updated each time communication with the person is terminated.

11. An alert control method in telephone equipment having an alert function, comprising the steps of:

20 a) storing time data related to a name of a person to communicate with in a phonebook database;

b) storing an alert-inhibition time period during

002259 4788980

FQ5-488

31

which alert is inhibited:

c) determining based on the time data whether a predetermined time interval has elapsed without communicating with the person;

5 d) alerting when a current time of day falls out of
the alert-inhibition time period and it is determined that the
predetermined time interval has elapsed without communicating
with the person; and

e) inhibiting alert when the current time of day falls into the alert-inhibition time period even if it is determined that the predetermined time interval has elapsed without communicating with the person.

12. The alert control method according to claim 11,
wherein the time data is a last-communication time of day at which
15 communication with the person was made last.

13. The alert control method according to claim 11, wherein the alerting of the step (d) is performed by driving at least one of a speaker, a vibrator, and a display.

14. The alert control method according to claim 13,
20 wherein, in the step (e), an audible alert by the speaker and/or
the vibrator is inhibited and a silent alert on the display is
permitted.

PQ5-488

32

15. The alert control method according to claim 1,
further comprising the steps of:

d) storing an alert list containing persons targeted
for alert;

5 e) displaying the alert list in form of a menu on
a display so that a desired one is selected from the alert list
to make a call to the desired one.

16. The alert control method according to claim 8,
further comprising the steps of:

10 f) storing an alert list containing persons targeted
for alert;

g) displaying the alert list in form of a menu on
a display so that a desired one is selected from the alert list
to make a call to the desired one.

15 17. The alert control method according to claim 11,
further comprising the steps of:

f) storing an alert list containing persons targeted
for alert;

20 g) displaying the alert list in form of a menu on
a display so that a desired one is selected from the alert list
to make a call to the desired one.

002250 24869550

FQ5-468

33

18. A telephone apparatus having an alert function,
comprising:

a phonebook database for storing time data related to a name of a person to communicate with; and

5 a controller for determining based on the time data whether a predetermined time interval has elapsed without communicating with the person and starting the alert function when it is determined that the predetermined time interval has elapsed without communicating with the person.

10 19. A telephone apparatus having an alert function,
 comprising:

a phonebook database for storing a last-communication time of day related to a name of each of a plurality of persons to communicate with, wherein the plurality of persons
15 is divided into a plurality of groups; and

a controller for determining a before-alert time interval for each of the groups, wherein the before-alert time interval is a time interval during which communication with the person is not made before alerting, determining whether the before-alert time interval has elapsed after the last-communication time of day, and starting the alert function when it is determined that the before-alert time interval has elapsed after the last-communication time of day.

FQ5-488

34

20. A telephone apparatus having an alert function,
comprising:

a phonebook database for storing time data related to a name of a person to communicate with;

5 an alert-inhibition timetable storing an alert-inhibition time period during which alert is inhibited; and

a controller for determining based on the time data whether a predetermined time interval has elapsed without communicating with the person, starting the alert function when a current time of day falls out of the alert-inhibition time period and it is determined that the predetermined time interval has elapsed without communicating with the person, and inhibiting alert when the current time of day falls into the alert-inhibition time period even if it is determined that the predetermined time interval has elapsed without communicating with the person.

FQ5-488

3 5

ABSTRACT


An alert control method in telephone equipment allowing communication with a certain person to be ensured is disclosed. A last-communication time of day related to a name of a person to communicate with is stored in a phonebook database. It is
5 determined whether a predetermined time interval has elapsed after the last-communication time of day without communicating with the person. When it is determined that the predetermined time interval has elapsed without communicating with the person, an audible or silent alert is made to alert the user to make a
10 call to that person.

002250 14859950

FQ5-488

1/14


FIG. 1



FQ5-488

2/14


FIG. 2



FQ5-488

3/14


FIG. 3



FQ5-488

4/14


FIG. 4



FQ5-488

5/14


FIG. 5



FQ5-488

6/14

FIG. 6



FQ5-488

7/14

FIG. 7

110 PHONEBOOK DATABASE

No.	PHONE NUM.	NAME	LAST-ACCESS TIME OF DAY	GROUP	BEFORE-ALERT TIME INTERVAL
1	03-1234-5678	YAMADA TARO	1999/05/31/10:10	CLIENT	3 DAYS
2	090-1192-1274	SUZUKI ICHIRO	1999/05/31/19:05	FRIEND	15 HOURS
3	070-4416-5525	NISHIDA HIKARI	1999/05/31/15:22	FRIEND	1 MONTH
4	045-123-4567	SATO EISAKU	1999/04/25/15:23	CLIENT	NO SETTING(NO ALERT)
5	0422-12-3456	NISHIYAMA MITSUO	1999/04/25/15:24	FRIEND	NO SETTING(NO ALERT)
.
.


FQ5-488

8/14

FIG. 8

GROUP	BEFORE-ALERT TIME INTERVAL
CLIENT	3 DAYS
FRIEND	15 HOURS
COMPANY	1 WEEK
⋮	⋮

FIG. 9



002260-4869960

FQ5-488

9/14

FIG. 10

110 PHONEBOOK DATABASE

No.	PHONE NUM.	NAME	LAST-ACCESS TIME OF DAY	GROUP	BEFORE-ALERT TIME INTERVAL
1	03-1234-5678	YAMADA TARO	1999/05/31/10:10	CLIENT	3 DAYS
2	090-1192-1274	SUZUKI ICHIRO	1999/05/31/19:05	FRIEND	15 HOURS
3	070-4416-5525	NISHIDA HIKARI	1999/05/31/15:22	FRIEND	15 HOURS
4	045-123-4567	SATO EISAKU	1999/04/25/15:23	CLIENT	3 DAYS
5	0422-12-3456	NISHIYAMA MITSUO	1999/04/25/15:24	FRIEND	15 HOURS
.
.

FQ5-488

10/14

FIG. 11

120 ALERT-INHIBITION TIME TABLE


SETTING No.	ALERT-INHIBITION TIME
1	00:00~08:00
2	1999/05/25/13:00~1999/05/25/17:00
⋮	⋮

002260 24969560

FQ5-488

11/14

FIG. 12



FQ5-488

12/14

FIG. 13





FIG. 14



FQ5-488

13/14

FIG. 15




FIG. 16


130 ALERT LIST

No.	PHONE NUMBER	NAME
1	03-1234-5678	YAMADA TARO
2	090-1192-1274	SUZUKI ICHIRO
⋮	⋮	⋮

FQ5-488

14/14

FIG. 17



002250 2485950

11-273099

FOS-488 (157)

Application for United States Patent

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

TELEPHONE APPARATUS AND ALERT CONTROL METHOD

the specification of which:

(check one)

☒ is attached hereto

☐ was filed on _____, as
Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56*

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Prior Foreign Application(s)		27/09/1999	priority claimed
273099/1999	Japan	27/09/1999	X
(Number)	(Country)	(Day/Month/Year Filed)	yes no
(Number)	(Country)	(Day/Month/Year Filed)	yes no
(Number)	(Country)	(Day/Month/Year Filed)	yes no

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

Power of Attorney: As a named inventor, I hereby appoint Sean M. McGinn, Reg. 34,386, and Frederick W. Gibb, III, Reg. No. 37,629 as attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. All correspondence should be directed to McGinn & Gibb, P.C., 1701 Clarendon Boulevard, Suite 100, Arlington, Virginia 22209. Telephone calls should be directed to McGinn & Gibb, P.C. at (703) 294-6699.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful

false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole
or First Inventor

YOICHI OKANO

Inventor's Signature

Yoichi Okano



Date September 21, 2000

Residence

Tokyo, Japan

Citizenship

Japanese

Post Office Address

c/o NEC Corporation, 7-1, Shiba 5-chome, Minato-ku, Tokyo, Japan

Full Name of Second

Joint Inventor, If Any

Inventor's Signature

Date

Residence

Citizenship

Post Office Address

Full Name of Third

Joint Inventor, If Any

Inventor's Signature

Date

Residence

Citizenship

Post Office Address

Full Name of Fourth

Joint Inventor, If Any

Inventor's Signature

Date

Residence

Citizenship

Post Office Address

(An additional sheet(s) is/are attached hereto if the present invention includes more than four inventors.)

*Title 37, Code of Federal Regulations, § 1.56:

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith toward the Patent and Trademark Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and (1) it establishes, by itself or in combination with other information, a prima facie case of unpatentability; or (2) it refutes, or is inconsistent with, a position the applicant takes in: (i) opposing an argument of unpatentability relied on by the Office, or (ii) asserting an argument of patentability.

002260 24269960